

Care.

Trust.

Responsibility.



M2-POS

All-In-One Mobile POS

Features At-A-Glance

Integrated Thermal Receipt Printer

Integrated 3 Track MSR

Integrated Barcode Scanner

Integrated IC Smart Card Reader



Specifications

| Item | M2-POS |
|--------------------------------|--|
| Processor | Intel Xscale PXA 270 : 520MHz |
| Display | 3.5" TFT LCD with touch screen, 260k color, (240 x 320) |
| System Memory | 64MB NOR, 64MB NAND, 128MB SDRAM |
| Telecom Standards | Quad-band GSM / GPRS or CDMA |
| Communication | Wifi 802.11 b/g, Bluetooth 2.0 class 2 (profile: SPP) |
| Printer | 2" thermal printer (3.14" per second) |
| MSR | 1,2,3 track supported (bi-directional) |
| IC Card ^{***} | IC card EMV2000 Level 1,2 certified (4 SAM slots) |
| Barcode Scanner ^{***} | 1D |
| Camera ^{***} | 2 Megapixel |
| Extension Slot | microSD card |
| Drop Test | 4 ft |
| Operating Temperature | 32° F ~ 40° F |
| Storage Temperature | -4° F ~ 122° F |
| Interface | Mini-USB 2.0 |
| Battery | Rechargeable Li-ion battery 7.4V (1900mAh) |
| Cradle | RS232C * 2 ports, USB host & slave ports, mini-USB, battery slot charger |
| Dimensions | 3" (W) x 8.7" (L) x 1.31" (H) |
| Weight | Standard model 0.90 lb without battery (Battery : 0.19 lb) |
| Other | Earphone jack & speaker |

^{***}Optional Upgrade

Features In Detail



M2-POS Cradle



Cradle Ports:

- mini USB
- USB 1.1
- standard USB
- 2 Serial (RS232)



www.partnertechcorp.com

Partner Tech USA • 51 Parker • Irvine • CA • 92618 • Tel: (949) 598-1888 • Fax: (949) 598-0088

© 2010 Partner Tech USA. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Features and specifications are subject to change without notice. All weights and measurements are approximate.